

Refrigerators and freezers



ProfiLine



ProfiPremiumLine



Performance series

Perfection series

	ProfiLine
	GKPV/GGPV
Environmental conditions	Appliances with foamed door: Climate class 5: Appliances with glass door GKPV 6573: Climate class 5:
Temperature stability	EN 16825 Refrigerators: +1 to +15°C / -2 to +15°C Freezers: -10 to -26°C Refrigerators: Class M1 Freezers: Class L1 Refrigerators: with 3 humidity zones Freezers: with NoFrost
Storage safety	Visual and audible alarms Power failure alarm Self-closing door < 90° Mechanical lock
Interfaces	RS485 (optional)
Features	LED 7-segment display with buttons Fridges: GN 2/1, 650 × 530 mm (lengthwise insertion) Freezers: GN 2/1, 650 × 530 mm (lengthwise insertion) Castors as accessory, with adjustable feet as standard Refrigerators: Glass door models with ceiling lighting Full-length integrated handle
Energy consumption	SuperEfficient EU directive 2015/1094
Compliance	Safety machinery directive – EN 60335

ProfiPremiumLine

	GKPV/GGPV
	Appliances with foamed door: Climate class 5:
	EN 16825 Refrigerators: +1 to +15°C / -2 to +15°C Freezers: -10 to -26°C Refrigerators: Class M1 Freezers: Class L1 Refrigerators: with 3 humidity zones Freezers: with NoFrost Visual and audible alarms Power failure alarm Self-closing door < 90° Mechanical lock
	RS485
	LED 7-segment display with buttons Fridges: GN 2/1, 650 × 530 mm (lengthwise insertion) Freezers: GN 2/1, 650 × 530 mm (lengthwise insertion) Castors as accessory, with adjustable feet as standard Full-length integrated handle
	SuperEfficient EU directive 2015/1094
	Safety machinery directive – EN 60335

Performance series

	FRFvg/FFFsg
	Appliances with foamed door: Climate class 5:
	EN 16825 Refrigerators: +1 to +15°C Freezers: -9 to -26°C Refrigerators: Class M1 Freezers: Class L1 Refrigerators: with 3 humidity zones Freezers: with SmartFrost Visual and audible alarms Power failure alarm Self-closing door at < 90° Mechanical lock
	LAN/WiFi optional (SmartModule) Local AP optional
	Monochrome display, touch buttons Refrigerators: 75 cm wide: GN 2/1, 650 × 530 mm (crosswise insertion) Freezers: 75 cm wide: Euronorm 600 × 400 mm (crosswise insertion) Individually adjustable maintenance timer Castors/adjustable feet as accessory, 75 cm wide appliances with adjustable feet as standard
	Aluminium door handle
	SuperEfficient EU directive 2015/1094 FFFsg no label
	Safety machinery directive – EN 60335

Perfection series

	FRFCvg/FFFCvg/FFFCsg
	Appliances with foamed door: Climate class 5: Appliances with glass door: Climate class 4:
	EN 16825 Refrigerators: +1 to +15°C / -2 to +15°C Freezers: -9 to -26°C Refrigerators: Class M1 Freezers: Class L1 Refrigerators: with 3 humidity zones Freezers: with SmartFrost and NoFrost Visual and audible alarms Power failure alarm Self-closing door at < 90° Mechanical lock
	LAN/WiFi optional (SmartModule) Local AP optional
	Monochrome display, touch buttons Refrigerators: 75 cm wide: GN 2/1, 650 × 530 mm (crosswise insertion) Freezers: 75 cm wide: Euronorm 600 × 400 mm (crosswise insertion) Individually adjustable maintenance timer Castors/adjustable feet as accessory, 75 cm wide appliances with adjustable feet as standard Evaporator cover (stops items freezing onto inner liner), only for glass door models, optional for insulating door models
	Refrigerators: Insulating and glass door models with ceiling lighting Freezers: LED lighting in the front housing Aluminium door handle
	SuperEfficient EU directive 2015/1094 FFFCsg no label
	Safety machinery directive – EN 60335