

Refrigerators and freezers



ProfiLine



Performance series

	ProfiLine BKPv/BGPv	Performance series BRFvg/BFFsg
Environmental conditions	Appliances with foamed door: Climate class 5:	Appliances with foamed door: Climate class 5:
Temperature stability	EN 16825 Refrigerators: -5 to +15°C Freezers: -10 to -35°C Refrigerators: Class M1 Freezers: Class L1 Refrigerators: with 3 humidity zones Freezers: with NoFrost	EN 16825 Refrigerators: +1 to +15°C Freezers: -9 to -26°C Refrigerators: Class M1 Freezers: Class L1 Refrigerators: with 3 humidity zones Freezers: with SmartFrost
Storage safety	Visual and audible alarms Power failure alarm Min./max. temperature display Self-closing door at < 90° Mechanical lock	Visual and audible alarms Power failure alarm Min./max. temperature display Self-closing door at < 90° Mechanical lock Transparent glass (BRFvg 5511)
Features	LED 7-segment display with buttons Refrigerators: Euronorm 600 × 800 mm (lengthwise insertion) at BKPv 8470/8420 Euronorm 400 × 600 mm (lengthwise insertion) at BKPv 6570/6520 Freezers: Euronorm 600 × 800 mm (lengthwise insertion) at BKPv 8470/8420 Euronorm 400 × 600 mm (lengthwise insertion) at BKPv 6570/6520 Castors as accessories, with adjustable feet as standard	Monochrome display, touch buttons Refrigerators: Euronorm 600 × 400 mm (crosswise insertion) Freezers: Euronorm 600 × 400 mm (crosswise insertion) Individually adjustable maintenance timer Castors/adjustable feet as accessories Evaporator cover (stops items freezing onto inner liner), only for glass door models, optional for insulating door models Glass door models with ceiling lighting
Energy consumption	Full-length integrated handle SuperEfficient EU directive 2015/1094	Aluminium door handle SuperEfficient EU directive 2015/1094
Compliance	Safety machinery directive – EN 60335	Safety machinery directive – EN 60335